

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Name:** Clear Plastic Polish

**Product Code:** 101758

#### Intended Use of the Product

**Use of the Substance/Mixture:** Polish.

#### Name, Address, and Telephone of the Responsible Party

##### Company

Star brite Inc.

4041 SW 47<sup>th</sup> Avenue

Fort Lauderdale, FL 33314

(954)587-6280

[www.starbrite.com](http://www.starbrite.com)

#### Emergency Telephone Number

**Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226

Skin Irrit. 2 H315

#### Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



**Signal Word (GHS-US)** : Warning

**Hazard Statements (GHS-US)** : H226 - Flammable liquid and vapor.  
H315 - Causes skin irritation.

**Precautionary Statements (GHS-US)** : P210 - Keep away from sparks, open flames, hot surfaces, heat - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof ventilating, lighting, electrical equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
P280 - Wear eye protection, protective gloves, protective clothing.  
P303+P361+P353+P352 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of water.  
P321 - Specific treatment (see Section 4).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

#### Other Hazards

Aquatic Chronic 3

H412 - Harmful to aquatic life with long lasting effects.

# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P273 - Avoid release to the environment.

### **Unknown Acute Toxicity (GHS-US)**

3.13 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral, Dermal, Inhalation)

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### **Mixture**

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Solvent naphtha, petroleum, medium aliphatic	(CAS No) 64742-88-7	10 - 15	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	1 - 5	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

## **SECTION 4: FIRST AID MEASURES**

### **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** Causes skin irritation.

**Inhalation:** May cause irritation to the respiratory tract.

**Skin Contact:** Causes skin irritation.

**Eye Contact:** May cause eye irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Do not allow run-off from fire fighting to enter drains or water courses. Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds. Silicon oxides.

**Reference to Other Sections** Refer to section 9 for flammability properties.

# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray). Keep away from open flames, hot surfaces and sources of ignition. No smoking.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Eliminate ignition sources. Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Stop leak if safe to do so.

**Environmental Precautions** Prevent entry to sewers and public waters.

#### Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

#### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

### SECTION 7: HANDLING AND STORAGE

#### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

#### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Store away from oxidizers, combustible materials, and all ignition sources.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Specific End Use(s)** Polish.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)		
USA ACGIH	TLV	Not applicable
USA OSHA	PEL	Not applicable
USA NIOSH	REL	Not applicable
USA NIOSH	IDLH	Not applicable

#### Exposure Controls

**Appropriate Engineering Controls:** Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases or vapors may be released. Use explosion-proof equipment.

**Personal Protective Equipment:** Protective clothing. Safety glasses. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Wear fire/flammable resistant/retardant clothing.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Other Information:** When using, do not eat, drink or smoke.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White opaque liquid
Odor	: Banana-like odor
Odor Threshold	: Not available
pH	: 9.25 - 9.35
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: -17.8 °C (0 °F)
Flash Point	: 55.6 °C (132 °F) Pensky-Martens Closed Cup (132.08 °F)
Auto-ignition Temperature	: -17.8 °C (0 °F)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density/Specific Gravity	: 0.973 - 0.975 (water = 1) at 0 °C (32 °F)
Solubility	: Soluble in water.
Partition Coefficient: N-octanol/water	: Not available
Viscosity	: 3300 cP at 25 °C (77 °F)
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Heat, hot surfaces, sparks, open flames, and other ignition sources.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation. (pH: 9.25 - 9.35)

**Serious Eye Damage/Irritation:** Not classified (pH: 9.25 - 9.35)

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not available

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause irritation to the respiratory tract.

# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Symptoms/Injuries After Skin Contact:** Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** Repeated or prolonged skin contact may cause dermatitis and defatting.

### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	> 5.28 mg/l/4h
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects.

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
LC50 Fish 1	800 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

**Persistence and Degradability** Not applicable

### Bioaccumulative Potential

Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
BCF Fish 1	(bioaccumulation expected)
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF Fish 1	61 - 159

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** EPA Hazardous Waste Number: D001 (Ignitability).

## SECTION 14: TRANSPORT INFORMATION

**In Accordance With ICAO/IATA/DOT/TDG/IMDG**

**UN Number** Not regulated. Does not sustain combustion according to ASTM D4206 or Appendix H of 49 CFR part 173.

**UN Proper Shipping Name** Not regulated.

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

Clear Plastic Polish	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard
Solvent naphtha, petroleum, medium aliphatic (64742-88-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations



<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard

### US State Regulations

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New Jersey - Special Health Hazards Substances List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term

### Canadian Regulations

<b>Clear Plastic Polish</b>	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class B Division 3 - Combustible Liquid
 	

<b>Solvent naphtha, petroleum, medium aliphatic (64742-88-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 01/21/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness


# Clear Plastic Polish

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
- NFPA Fire Hazard** : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS