

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: STAR TRON QUICK FIX

Product Code: 186XX

Intended Use of the Product

Fuel Additive

Name, Address, and Telephone of the Responsible Party

Company

Star brite Inc.
 4041 SW 47th Avenue
 Fort Lauderdale, FL 33314
 (954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 4 H227

Skin Sens. 1 H317

Asp. Tox. 1 H304

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H227 - Combustible liquid.
 H304 - May be fatal if swallowed and enters airways.
 H317 - May cause an allergic skin reaction.

Precautionary Statements (GHS-US)

: P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
 P261 - Avoid breathing mist, spray, vapors.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P280 - Wear eye protection, protective clothing, protective gloves, respiratory protection.
 P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.
 P302+P352 - If on skin: Wash with plenty of water.
 P321 - Specific treatment (see Section 4 on this SDS).
 P331 - Do NOT induce vomiting.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide (CO2), dry extinguishing powder, Water to extinguish.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Hazards

Aquatic Acute 2 H401

H401 - Toxic to aquatic life

P273 - Avoid release to the environment.

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. May cause drying or defatting of the skin.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Name | Product Identifier | % (w/w) | Classification (GHS-US) |
|---|--|---------|--|
| Petroleum distillates, hydrotreated light | (CAS No) 64742-47-8 (EC No) 926-141-6 | 65-90 | Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401 |
| Polymer* | | 10-25 | |

Full text of H-phrases: see section 16

* Product classification is being withheld as a trade secret. If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause an allergic reaction in sensitive individuals. Aspiration hazard.

Inhalation: May cause drowsiness or dizziness – symptoms can include: dizziness, nausea, vomiting, loss of coordination, and disorientation. Extreme exposures can cause respiratory depression, loss of consciousness.

Skin Contact: May cause an allergic skin reaction.

Eye Contact: May cause eye irritation.

Ingestion: May be fatal if swallowed and enters airways. Ingestion may cause narcotic effects including, but not limited to: nausea, vomiting, abdominal pain, dizziness, incoordination, and respiratory depression.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry powder, alcohol-resistant foam, water spray or fog in large amounts, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible liquid. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Do not allow run-off from firefighting to enter drains or water courses. Do not breathe fumes from fires or vapors from decomposition.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Avoid all eyes and skin contact and do not breathe vapor and mist. Use only outdoors or in a well-ventilated area.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Store locked up. Keep cool. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s) Fuel Additive

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Petroleum distillates, hydrotreated light (64742-47-8)

| | | |
|-------------------------|------------------------------|--|
| British Columbia | OEL TWA (mg/m ³) | 200 mg/m ³ (application restricted to conditions in which |
|-------------------------|------------------------------|--|

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

there are negligible aerosol exposures)

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases or vapors may be released. Ground/bond container and receiving equipment. Use explosion-proof equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective goggles. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically and fire/flame resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | |
|---|---|
| Physical State | : Liquid |
| Appearance | : Slight amber |
| Odor | : Characteristic |
| Odor Threshold | : Not available |
| pH | : Not available |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : > 100 °C (> 212°F) |
| Flash Point | : 69 °C (156.20 °F) |
| Auto-ignition Temperature | : Not available |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not available |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20 °C | : Not available |
| Relative Density | : 0.8 (at 20° C) |
| Specific Gravity | : Not available |
| Solubility | : Not soluble in water |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |
| Explosion Data – Sensitivity to Mechanical Impact | : Not expected to present an explosion hazard due to mechanical impact. |
| Explosion Data – Sensitivity to Static Discharge | : Not expected to present an explosion hazard due to static discharge. |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Chemical Stability: Combustible liquid. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Overheating. Sources of ignition. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). May release flammable gases and organic vapors.

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

ID50 and IC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause drowsiness or dizziness – symptoms can include: dizziness, nausea, vomiting, loss of coordination, and disorientation. Extreme exposures can cause respiratory depression, loss of consciousness.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways. Ingestion may cause narcotic effects including, but not limited to: nausea, vomiting, abdominal pain, dizziness, incoordination, and respiratory depression.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

ID50 and IC50 Data:

| Petroleum distillates, hydrotreated light (64742-47-8) | |
|--|---------------|
| ID50 Oral Rat | > 5000 mg/kg |
| ID50 Dermal Rabbit | > 2000 mg/kg |
| IC50 Inhalation Rat | > 5.2 mg/l/4h |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

| Petroleum distillates, hydrotreated light (64742-47-8) | |
|--|---|
| IC50 Fish 1 | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| IC 50 Fish 2 | 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |

Persistence and Degradability

| STAR TRON QUICK FIX | |
|-------------------------------|------------------|
| Persistence and Degradability | Not established. |

Bioaccumulative Potential

| STAR TRON QUICK FIX | |
|---------------------------|------------------|
| Bioaccumulative Potential | Not established. |

| Petroleum distillates, hydrotreated light (64742-47-8) | |
|--|----------|
| BCF Fish 1 | 61 - 159 |

Mobility in Soil: Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Hazardous waste due to toxicity.

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number

DOT NA no. : NA1993
UN-No. (TDG) : Not regulated
UN-No. (IMDG) : Not regulated
UN-No. (IATA) : Not regulated

UN Proper Shipping Name

Proper Shipping Name (DOT) : COMBUSTIBLE LIQUID, N.O.S. (Petroleum Distillates)
Transport Document Description (DOT) : NA1993 COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM DISTILLATES), 3, III

Transport Hazard Class(es)

Department Of Transportation (DOT) Hazard Classes : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
DOT Symbols : D - Proper shipping name for domestic use only, G - Identifies PSN requiring a technical name

Packing Group (DOT)

DOT Special Provisions (49 CFR 172.102) : III - Minor Danger
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2).
Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 Cfr 173.xxx) : 150
DOT Packaging Non Bulk (49 Cfr 173.xxx) : 203
DOT Packaging Bulk (49 Cfr 173.xxx) : 241
Explosive Limit And Limited Quantity Index : 5
Marine Pollutant : No

Additional Information

Emergency Response Guide (ERG) Number : 128

Other Information : This product meets the limited quantity exceptions as follows: DOT: Not regulated as dangerous goods except when shipped in bulk. Otherwise, the above descriptions apply.

Transport by sea

Dot Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : 60 L
DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 220 L

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| | |
|---|--|
| STAR TRON QUICK FIX | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Fire hazard |
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard |

STAR TRON QUICK FIX

Safety Data Sheet



According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

| |
|---|
| Polymer |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |

US State Regulations

| |
|---|
| Petroleum distillates, hydrotreated light (64742-47-8) |
| U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour |
| U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual |
| U.S. - Texas - Effects Screening Levels - Long Term |
| U.S. - Texas - Effects Screening Levels - Short Term |

Canadian Regulations

| | |
|---|--|
| STAR TRON QUICK FIX | |
| WHMIS Classification | Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|   | |

| | |
|---|--|
| Petroleum distillates, hydrotreated light (64742-47-8) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

| | |
|---|--------------|
| Polymer | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| WHMIS Classification | Trade Secret |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.


SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 08/24/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|-----------------|--|
| Aquatic Acute 2 | Hazardous to the aquatic environment - Acute Hazard Category 2 |
| Asp. Tox. 1 | Aspiration hazard Category 1 |
| Flam. Liq. 4 | Flammable liquids Category 4 |
| Skin Sens. 1 | Skin sensitization Category 1 |
| H227 | Combustible liquid |
| H304 | May be fatal if swallowed and enters airways |
| H317 | May cause an allergic skin reaction |
| H401 | Toxic to aquatic life |

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA Fire Hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®
(954)587-6280

STAR TRON QUICK FIX

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2