

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Premium RV Rubber Seal Conditioner

**Product Code:** 761XX

### Intended Use of the Product

Protectant

### Name, Address, and Telephone of the Responsible Party

#### Company

Star brite Inc.

4041 SW 47<sup>th</sup> Avenue

Fort Lauderdale, FL 33314

(954)587-6280

[www.starbrite.com](http://www.starbrite.com)

### Emergency Telephone Number

**Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### Classification (GHS-US)

Eye Dam. 1 H318

Full text of H-phrases: see section 16

### Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)

:



#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H318 - Causes serious eye damage.

#### Precautionary Statements (GHS-US)

: P280 - Wear eye protection, protective clothing, protective gloves.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 - Immediately call a POISON CENTER, a doctor.  
 P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. May be corrosive to respiratory tract.

#### Aquatic Chronic 3 H412

H412 - Harmful to aquatic life with long lasting effects.

P273 - Avoid release to the environment.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
2,6,8-Trimethyl-4-nonyl polyethylene glycol ether	(CAS No) 60828-78-6	4.975 - 14.925	Eye Dam. 1, H318 Aquatic Chronic 3, H412
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-	(CAS No) 67674-67-3	3.4825 - 6.4675	Acute Tox. 4 (Inhalation:dust,mist), H332

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

tetramethyl-1-[(trimethylsilyloxy)disiloxanyl]propyl]-.omega.-hydroxy-			Eye Dam. 1, H318 Aquatic Chronic 2, H411
Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-[(1,1,3,3-tetramethylbutyl)phenoxy]-, sodium salt	(CAS No) 55348-40-8	0.24875 - 0.74625	Skin Irrit. 2, H315 Eye Dam. 1, H318
Polyethylene glycol	(CAS No) 25322-68-3	0.04975 - 0.4975	STOT SE 3, H335
Isopropyl alcohol	(CAS No) 67-63-0	0.04975 - 0.4975	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
n-Amyl acetate	(CAS No) 628-63-7	0.003 - 0.015	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	0.003 - 0.015	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER/doctor/physician if you feel unwell.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Seek medical attention immediately if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes serious eye damage.

**Inhalation:** May cause respiratory irritation. May be corrosive to the respiratory tract.

**Skin Contact:** May cause skin irritation.

**Eye Contact:** Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects. May cause irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** None expected under normal conditions of use.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Powder, alcohol-resistant foam, water spray, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not flammable.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water sources.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>).

**Other Information:** Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all unnecessary exposure. Do not breathe vapor, mist or spray.

#### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

### Environmental Precautions

Prevent entry to sewers and public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

### Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## **SECTION 7: HANDLING AND STORAGE**

### Precautions for Safe Handling

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product.

### Conditions for Safe Storage, Including Any Incompatibilities

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Alkalis.

**Specific End Use(s)** Protectant

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

<b>Isopropyl alcohol (67-63-0)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	400 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	980 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	400 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	1225 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	500 ppm

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA IDLH</b>	<b>US IDLH (ppm)</b>	<b>2000 ppm (10% LEL)</b>
<b>Alberta</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>984 mg/m<sup>3</sup></b>
<b>Alberta</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Alberta</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>492 mg/m<sup>3</sup></b>
<b>Alberta</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>British Columbia</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>British Columbia</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Manitoba</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Manitoba</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>New Brunswick</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>1230 mg/m<sup>3</sup></b>
<b>New Brunswick</b>	<b>OEL STEL (ppm)</b>	<b>500 ppm</b>
<b>New Brunswick</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>983 mg/m<sup>3</sup></b>
<b>New Brunswick</b>	<b>OEL TWA (ppm)</b>	<b>400 ppm</b>
<b>Newfoundland &amp; Labrador</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Newfoundland &amp; Labrador</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Nova Scotia</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Nova Scotia</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Nunavut</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>1228 mg/m<sup>3</sup></b>
<b>Nunavut</b>	<b>OEL STEL (ppm)</b>	<b>500 ppm</b>
<b>Nunavut</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>983 mg/m<sup>3</sup></b>
<b>Nunavut</b>	<b>OEL TWA (ppm)</b>	<b>400 ppm</b>
<b>Northwest Territories</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>1228 mg/m<sup>3</sup></b>
<b>Northwest Territories</b>	<b>OEL STEL (ppm)</b>	<b>500 ppm</b>
<b>Northwest Territories</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>983 mg/m<sup>3</sup></b>
<b>Northwest Territories</b>	<b>OEL TWA (ppm)</b>	<b>400 ppm</b>
<b>Ontario</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Ontario</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Prince Edward Island</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Prince Edward Island</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Québec</b>	<b>VECD (mg/m<sup>3</sup>)</b>	<b>1230 mg/m<sup>3</sup></b>
<b>Québec</b>	<b>VECD (ppm)</b>	<b>500 ppm</b>
<b>Québec</b>	<b>VEMP (mg/m<sup>3</sup>)</b>	<b>985 mg/m<sup>3</sup></b>
<b>Québec</b>	<b>VEMP (ppm)</b>	<b>400 ppm</b>
<b>Saskatchewan</b>	<b>OEL STEL (ppm)</b>	<b>400 ppm</b>
<b>Saskatchewan</b>	<b>OEL TWA (ppm)</b>	<b>200 ppm</b>
<b>Yukon</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>1225 mg/m<sup>3</sup></b>
<b>Yukon</b>	<b>OEL STEL (ppm)</b>	<b>500 ppm</b>
<b>Yukon</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>980 mg/m<sup>3</sup></b>
<b>Yukon</b>	<b>OEL TWA (ppm)</b>	<b>400 ppm</b>

### n-Amyl acetate (628-63-7)

<b>USA ACGIH</b>	<b>ACGIH TWA (ppm)</b>	<b>50 ppm</b>
<b>USA ACGIH</b>	<b>ACGIH STEL (ppm)</b>	<b>100 ppm</b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (mg/m<sup>3</sup>)</b>	<b>525 mg/m<sup>3</sup></b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (ppm)</b>	<b>100 ppm</b>
<b>USA NIOSH</b>	<b>NIOSH REL (TWA) (mg/m<sup>3</sup>)</b>	<b>525 mg/m<sup>3</sup></b>
<b>USA NIOSH</b>	<b>NIOSH REL (TWA) (ppm)</b>	<b>100 ppm</b>
<b>USA IDLH</b>	<b>US IDLH (ppm)</b>	<b>1000 ppm</b>
<b>Alberta</b>	<b>OEL STEL (mg/m<sup>3</sup>)</b>	<b>532 mg/m<sup>3</sup></b>
<b>Alberta</b>	<b>OEL STEL (ppm)</b>	<b>100 ppm</b>
<b>Alberta</b>	<b>OEL TWA (mg/m<sup>3</sup>)</b>	<b>266 mg/m<sup>3</sup></b>
<b>Alberta</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>British Columbia</b>	OEL STEL (ppm)	100 ppm
<b>British Columbia</b>	OEL TWA (ppm)	50 ppm
<b>Manitoba</b>	OEL STEL (ppm)	100 ppm
<b>Manitoba</b>	OEL TWA (ppm)	50 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	532 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	100 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	100 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	50 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	100 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	50 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	800 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	150 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	530 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	100 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	800 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	150 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	530 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	100 ppm
<b>Ontario</b>	OEL STEL (ppm)	100 ppm
<b>Ontario</b>	OEL TWA (ppm)	50 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	100 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	50 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	532 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	100 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	50 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	100 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	50 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	780 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	150 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	100 ppm
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>		
<b>British Columbia</b>	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (application restricted to conditions in which there are negligible aerosol exposures)

### Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

**Other Information:** When using, do not eat, drink or smoke.

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White Emulsion
Odor	: Pleasant
Odor Threshold	: Not available
pH	: 8
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: > 100 °C (212.0 °F)
Flash Point	: > 100 °C (212.0 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.09
Solubility	: Emulsifiable
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Sources of ignition. Incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Alkalis.

**Hazardous Decomposition Products:** Thermal decomposition generates : Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Formaldehyde. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**ID50 and IC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**pH:** 8

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**pH:** 8

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May cause respiratory irritation. May be corrosive to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects. May cause irritation to the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** None expected under normal conditions of use.

### Information on Toxicological Effects - Ingredient(s)

#### ID50 and IC50 Data:

<b>2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)</b>	
<b>ID50 Dermal Rabbit</b>	4780 µl/kg
<b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyloxy]disiloxanyl)propyl]-.omega.-hydroxy- (67674-67-3)</b>	
<b>ATE US (dust, mist)</b>	1.50 mg/l/4h
<b>Polyethylene glycol (25322-68-3)</b>	
<b>ID50 Oral Rat</b>	47000 mg/kg
<b>ID50 Dermal Rabbit</b>	> 20 ml/kg
<b>Isopropyl alcohol (67-63-0)</b>	
<b>ID50 Oral Rat</b>	4710 mg/kg
<b>ID50 Dermal Rabbit</b>	4059 mg/kg
<b>IC50 Inhalation Rat</b>	72600 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
<b>ID50 Oral Rat</b>	> 5000 mg/kg
<b>ID50 Dermal Rabbit</b>	> 2000 mg/kg
<b>IC50 Inhalation Rat</b>	> 5.2 mg/l/4h
<b>Isopropyl alcohol (67-63-0)</b>	
<b>IARC Group</b>	3

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Harmful to aquatic life.

<b>Isopropyl alcohol (67-63-0)</b>	
<b>LC50 Fish 1</b>	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 Daphnia 1</b>	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>EC50 Other Aquatic Organisms 1</b>	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
<b>LC 50 Fish 2</b>	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Other Aquatic Organisms 2</b>	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
<b>n-Amyl acetate (628-63-7)</b>	
<b>LC50 Fish 1</b>	650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
<b>LC50 Fish 1</b>	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>IC 50 Fish 2</b>	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

### Persistence and Degradability

<b>Premium RV Rubber Seal Conditioner</b>	
<b>Persistence and Degradability</b>	Not established.

### Bioaccumulative Potential

<b>Premium RV Rubber Seal Conditioner</b>	
<b>Bioaccumulative Potential</b>	Not established.

<b>Isopropyl alcohol (67-63-0)</b>	
<b>Log Pow</b>	0.05 (at 25 °C)

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
<b>BCF Fish 1</b>	61 - 159

**Mobility in Soil** Not available

### **Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Additional Information:** This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## **SECTION 14: TRANSPORT INFORMATION**

**In Accordance With ICAO/IATA/DOT/TDG/IMDG**

**UN Number** Not regulated for transport

**UN Proper Shipping Name** Not regulated for transport

**Transport Hazard Class(es)** Not regulated for transport

**Additional Information** Not available

**Transport by sea** Not regulated for transport

**Marine pollutant:** No

**Air transport** Not regulated for transport

## **SECTION 15: REGULATORY INFORMATION**

### **US Federal Regulations**

<b>Premium RV Rubber Seal Conditioner</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard
<b>2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyloxy)disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-[(1,1,3,3-tetramethylbutyl)phenoxy]-, sodium salt (55348-40-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Polyethylene glycol (25322-68-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Isopropyl alcohol (67-63-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 % (only if manufactured by the strong acid process, no supplier notification)
<b>n-Amyl acetate (628-63-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard

### **US State Regulations**

<b>2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)</b>	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	



# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### **Polyethylene glycol (25322-68-3)**

U.S. - Minnesota - Hazardous Substance List  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term

### **Isopropyl alcohol (67-63-0)**

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute  
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic  
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Connecticut - Volatile Substances  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Michigan - Occupational Exposure Limits - STELs  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - STELs  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
U.S. - New Jersey - Environmental Hazardous Substances List  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour  
U.S. - Tennessee - Occupational Exposure Limits - STELs  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - STELs  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

### **n-Amyl acetate (628-63-7)**

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Louisiana - Reportable Quantity List for Pollutants

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
 U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
 U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
 U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
 RTK - U.S. - Massachusetts - Right To Know List  
 U.S. - Michigan - Occupational Exposure Limits - TWAs  
 U.S. - Michigan - Polluting Materials List  
 U.S. - Minnesota - Hazardous Substance List  
 U.S. - Minnesota - Permissible Exposure Limits - TWAs  
 U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
 RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - New Jersey - Special Health Hazards Substances List  
 U.S. - New York - Occupational Exposure Limits - TWAs  
 U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour  
 U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
 U.S. - Oregon - Permissible Exposure Limits - TWAs  
 RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
 U.S. - Tennessee - Occupational Exposure Limits - TWAs  
 U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term  
 U.S. - Vermont - Permissible Exposure Limits - TWAs  
 U.S. - Washington - Permissible Exposure Limits - STELs  
 U.S. - Washington - Permissible Exposure Limits - TWAs  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater  
 U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

### Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour  
 U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual  
 U.S. - Texas - Effects Screening Levels - Long Term  
 U.S. - Texas - Effects Screening Levels - Short Term

### Canadian Regulations

#### Premium RV Rubber Seal Conditioner

WHMIS Classification	Class E - Corrosive Material
----------------------	------------------------------



#### 2,6,8-Trimethyl-4-nonyl polyethylene glycol ether (60828-78-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class E - Corrosive Material
----------------------	------------------------------

#### Poly(oxy-1,2-ethanediyl), .alpha.-[3-[1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl]propyl]-.omega.-hydroxy- (67674-67-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material
----------------------	-------------------------------------------------------------------------------------------------------------------------------

# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Poly(oxy-1,2-ethanediyl), -alpha.-sulfo.-omega.-[(1,1,3,3-tetramethylbutyl)phenoxy]-, sodium salt (55348-40-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class E - Corrosive Material Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Polyethylene glycol (25322-68-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Isopropyl alcohol (67-63-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>n-Amyl acetate (628-63-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 03/19/2015  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4


# Premium RV Rubber Seal Conditioner

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

- NFPA Health Hazard** : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
- NFPA Fire Hazard** : 0 - Materials that will not burn.
- NFPA Reactivity** : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2