

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 05/20/2016 Date of issue: 10/03/2014

Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: SB Home Teak Cleaner & Brightener Product Code: 136032 Intended Use of the Product

Use of the Substance/Mixture: Cleaner. Name, Address, and Telephone of the Responsible Party

Name, Address, and Te Starbrite[®] Inc. 4041 SW 47th Avenue Fort Lauderdale, FL 33314 (954)587-6280

www.starbrite.com

Emergency Telephone Number Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or MixtureGHS-US classificationEye Dam. 1 H318Full text of hazard classes and H-statements : see section 16Label ElementsGHS-US LabelingHazard Pictograms (GHS-US):

	CHS05
Signal Word (GHS-US)	: Danger
Hazard Statements (GHS-US)	: H318 - Causes serious eye damage.
Precautionary Statements (GHS-US)	: P280 - Wear eye protection, protective gloves, protective clothing.
-	P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P310 - Immediately call POISON CENTER/doctor.

Other Hazards

May be corrosive to respiratory tract. Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	GHS-US classification
Oxalic acid	(CAS No) 144-62-7	5 - 10	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Eye Dam. 1, H318
Hydroxyacetic acid	(CAS No) 79-14-1	5 - 10	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Sulfonic acids, C14-16-alkane hydroxy and	(CAS No) 68439-57-6	1 - 2	Skin Irrit. 2, H315
C14-16-alkene, sodium salts			Eye Irrit. 2A, H319
05/90/9016 EFFT P CC EN	(English US)		1/1(

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

			Aquatic Acute 2, H401
Triethanolamine	(CAS No) 102-71-6	0.1 - 1	Not classified

Full text of H-phrases: see section 16

*A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Obtain medical attention. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand. If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive, however in contact with incompatabilities may release explosive hydrogen gas.

Reactivity: Hazardous reactions will not occur under normal conditions. Adding water to solution may generate large amounts of heat. Reacts exothermically with (some) bases.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO2). Nitrogen compounds. Sulfur compounds.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Emergency Procedures: Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Materials for Containment and Cleaning Up

For Containment: Cautiously neutralize spilled liquid. Absorb and/or contain spill with inert material, then place in suitable container. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13. See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Avoid breathing vapors, mist, and spray. Do not get in eyes, on skin, or on clothing.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers. Metals.

Specific End Use(s)

Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Oxalic acid (144-62-7)		
Mexico	OEL TWA (mg/m ³)	1 mg/m ³
Mexico	OEL STEL (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m ³
USA ACGIH	ACGIH STEL (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	500 mg/m ³
Alberta	OEL STEL (mg/m ³)	2 mg/m ³
Alberta	OEL TWA (mg/m ³)	1 mg/m ³
British Columbia	OEL STEL (mg/m³)	2 mg/m ³ (anhydrous)
British Columbia	OEL TWA (mg/m ³)	1 mg/m ³ (anhydrous)
Manitoba	OEL STEL (mg/m³)	2 mg/m ³
Manitoba	OEL TWA (mg/m ³)	1 mg/m ³
New Brunswick	OEL STEL (mg/m³)	2 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	1 mg/m ³
Newfoundland & Labrador	OEL STEL (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m ³
Nova Scotia	OEL STEL (mg/m³)	2 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	1 mg/m ³
Nunavut	OEL STEL (mg/m ³)	2 mg/m ³
Nunavut	OEL TWA (mg/m ³)	1 mg/m ³

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

8 8	, , , , , , , , , , , , , , , , , , ,	
Northwest Territories	OEL STEL (mg/m ³)	2 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	1 mg/m ³
Ontario	OEL STEL (mg/m ³)	2 mg/m ³
Ontario	OEL TWA (mg/m ³)	1 mg/m ³
Prince Edward Island	OEL STEL (mg/m³)	2 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	1 mg/m ³
Québec	VECD (mg/m ³)	2 mg/m ³
Québec	VEMP (mg/m ³)	1 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	2 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	1 mg/m ³
Yukon	OEL STEL (mg/m ³)	2 mg/m ³
Yukon	OEL TWA (mg/m ³)	1 mg/m ³
Triethanolamine (102-71-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	5 mg/m ³
Manitoba	OEL TWA (mg/m ³)	5 mg/m ³
New Brunswick	OEL TWA (mg/m³)	5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	5 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	5 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	3.1 mg/m ³
Ontario	OEL TWA (ppm)	0.5 ppm
Prince Edward Island	OEL TWA (mg/m³)	5 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³
T ()		

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective clothing. Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Other Information:** When using, do not eat, drink or smoke

Characteristic

Not available

other mormation. when using, u	not cat, units of shicke
SECTION 9: PHYSICAL AND CI	EMICAL PROPERTIES
Information on Basic Physical a	nd Chemical Properties
Physical State	: Liquid
Appearance	: Colorless

Odor Threshold

Odor

٠

•

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

pH	:	1.6
- Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	Not available
Flash Point	:	> 100 °C (> 212 °F)
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	1 (water = 1)
Solubility	:	Soluble in water.
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

<u>Reactivity</u>: Hazardous reactions will not occur under normal conditions. Adding water to solution may generate large amounts of heat. Reacts exothermically with (some) bases.

<u>Chemical Stability</u>: Stable under recommended handling and storage conditions (see section 7).

<u>Possibility of Hazardous Reactions</u>: Hazardous polymerization will not occur.

<u>Conditions to Avoid</u>: Direct sunlight, extremely high or low temperatures, and incompatible materials. Contact with metallic substances.

Incompatible Materials: Strong bases. Strong oxidizers. Metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Sulfur compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified.

pH: 1.6

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 1.6

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

12 00 min 2000 2 min		
Oxalic acid (144-62-7)		
ID50 Oral Rat	375 mg/kg	
ID50 Dermal Rat	20000 mg/kg	
Hydroxyacetic acid (79-14-1)		
ID50 Oral Rat	1950 mg/kg	
LC 50 Inhalation Rat	3.6 mg/l/4h	
LC 50 Inhalation Rat	1.76 mg/l/4h	
Triethanolamine (102-71-6)		
LD50 Oral Rat	6400 mg/kg	
ID50 Dermal Rabbit	> 2000 mg/kg	
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, so	odium salts (68439-57-6)	
ID50 Oral Rat	2310 mg/kg	
ID50 Dermal Rabbit	6300 mg/kg	
LC 50 Inhalation Rat	> 52 mg/l/4h	
Triethanolamine (102-71-6)		
IARC Group	3	
SECTION 12: ECOLOGICAL INFORMATION		

Toxicity

Ecology - General: Not classified.

8/			
Oxalic acid (144-62-7)			
EC50 Daphnia 1	125 - 150 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])		
Hydroxyacetic acid (79-14-1)			
IC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])		
EC50 Daphnia 1	44 mg/l		
Triethanolamine (102-71-6)			
IC50 Fish 1	10600 (10600 - 13000) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-		
	through])		
LC 50 Fish 2	1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
ErC50 (algae)	169 mg/l		
Sulfonic acids, C14-16-alkane hydroxy a	nd C14-16-alkene, sodium salts (68439-57-6)		
IC50 Fish 1	4.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])		
EC50 Daphnia 1	4.53 mg/l (Ceriodaphnia sp)		
IC 50 Fish 2	12.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])		
ErC50 (algae)	5.2 mg/l (Water quality - Marine Algal Growth Inhibition Test with Skeletonema costatum		
	and Phaeodactylum tricornutum)		
Persistence and Degradability			
SB Home Teak Cleaner & Brightener			
Persistence and Degradability	Not established.		
Bioaccumulative Potential			
SB Home Teak Cleaner & Brightener			
Bioaccumulative Potential	Not established.		
Oxalic acid (144-62-7)			
BCF Fish 1	(no bioaccumulation)		
Log Pow	-0.81 (at 30 °C)		
Hydroxyacetic acid (79-14-1)			
Log Pow	-1.11 (at 19 °C)		

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

According To Federal Register / Vol. 77, No. 58 / Mor	nday, March 26, 2012 / Rule	s And Regulations
Triethanolamine (102-71-6)		
BCF Fish 1	3.9	
Log Pow	-2.53	
Mobility in Soil Not available	•	
Other Adverse Effects		
Other Information: Avoid release to the	environment	
SECTION 13: DISPOSAL CONSIDER		
		in accordance with all local, regional, national, provincial, territorial
and international regulations	use of waste material	in accordance with an local, regional, national, provincial, territorial
	emain hazardous whe	n empty. Continue to observe all precautions.
Ecology – Waste Materials: Avoid release	e to the environment.	n empty. continue to observe un precutions.
SECTION 14: TRANSPORT INFORM		
In Accordance With ICAO/IATA/DOT/TD		
UN Number Not regulated for transpo		
UN Proper Shipping Name Not regu		
Transport Hazard Class(es)	lated for transport	
<u>Marine Pollutant</u>	. No	
Additional Information Not available	: No	
Transport by sea Not regulated for	•	
Air transport Not regulated for transp		
In Accordance With IMDG Not regulated	•	
In Accordance With IATA/ICAO Not reg	-	
In Accordance With TDG Not regulated	for transport	
SECTION 15: REGULATORY INFORM	AATION	
US Federal Regulations		
SB Home Teak Cleaner & Brightener		
SARA Section 311/312 Hazard Classes		Immediate (acute) health hazard
Oxalic acid (144-62-7)		
Listed on the United States TSCA (Toxic S	ubstances Control Act) inventory
EPA TSCA Regulatory Flag	ubstances control Act,	T - T - indicates a substance that is the subject of a Section 4 test
LIA ISCA Regulatory riag		rule under TSCA
Hydroxyacetic acid (79-14-1)		
Listed on the United States TSCA (Toxic S	ubstances Control Act) inventory
Triethanolamine (102-71-6)		
Listed on the United States TSCA (Toxic S	ubstances Control Act) inventory
Sulfonic acids, C14-16-alkane hydroxy an		
Listed on the United States TSCA (Toxic S	ubstances control Act,	
US State Regulations		
Oxalic acid (144-62-7)	mta IIIVa (20 min)	
U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr)		
U.S Idaho - Non-Carcinogenic Toxic Air		a Ambiant Concentrations
U.S Idaho - Non-Carcinogenic Toxic Air		
U.S Idaho - Occupational Exposure Limit		
RTK - U.S Massachusetts - Right To Kno		
U.S Michigan - Occupational Exposure 1		
U.S Michigan - Occupational Exposure 1		
U.S Minnesota - Hazardous Substance List		
U.S Minnesota - Permissible Exposure I		

U.S. - Minnesota - Permissible Exposure Limits - STELs

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
U.S Minnesota - Permissible Exposure Limits - TWAs
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S New Jersey - Right to Know Hazardous Substance List
U.S New Jersey - Special Health Hazards Substances List
U.S New York - Occupational Exposure Limits - TWAs
U.S North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S Oregon - Permissible Exposure Limits - TWAs
RTK - U.S Pennsylvania - RTK (Right to Know) List
U.S South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S Tennessee - Occupational Exposure Limits - STELs
U.S Tennessee - Occupational Exposure Limits - TWAs
U.S Texas - Effects Screening Levels - Long Term U.S Texas - Effects Screening Levels - Short Term
U.S Vermont - Permissible Exposure Limits - STELs
U.S Vermont - Permissible Exposure Limits - TWAs
U.S Washington - Permissible Exposure Limits - STELs
U.S Washington - Permissible Exposure Limits - TWAs
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Hydroxyacetic acid (79-14-1)
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term
Triethanolamine (102-71-6)
RTK - U.S Massachusetts - Right To Know List
U.S Minnesota - Hazardous Substance List
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
RTK - U.S New Jersey - Right to Know Hazardous Substance List
U.S North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
RTK - U.S Pennsylvania - RTK (Right to Know) List
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)
U.S Texas - Effects Screening Levels - Long Term
U.S Texas - Effects Screening Levels - Short Term
Canadian Regulations

SB Home Teak Cleaner & Brightener

1	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Oxalic acid (144-62-7)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 0.1 %		
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class E - Corrosive Material	
Hydroxyacetic acid (79-14-1)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
DL Concentration 1 %		
WHMIS Classification	Class E - Corrosive Material	
Triethanolamine (102-71-6)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

:05/20/2016

Revision Date		
Other Information		

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H401	Toxic to aquatic life
H402	Harmful to aquatic life

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

NFPA Health Hazard	3 - Short exposure could cause serious te residual injury even though prompt med given.	
NFPA Fire Hazard NFPA Reactivity	 0 - Materials that will not burn. 0 - Normally stable, even under fire expo and are not reactive with water. 	osure conditions,

Party Responsible for the Preparation of This Document **Starbrite**[®] Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS