



According to OSHA HazCom 2012, 29 CFR 1910.1200

### SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Premium Type C Gear Lube

Product code : 273XX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : Lubricants, greases, release agents.

1.3. Details of the supplier of the safety data sheet

Supplier : Star Brite

4041 SW 47th Avenue

33314 Fort Lauderdale, Florida, United States of America

Telephone : 1-800-327-8583

E-mail : vwaclawek@kinpakinc.com Website : http://www.starbrite.com

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:

US - Telephone : 1-703-527-3887 (During office hours only)

EMERGENCY TELEPHONE NUMBER (for DOCTORS only):

Chemtrec 1-703-527-3887 (24/7)

#### SECTION 2 HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

GHS Classification (HCS : Skin sensitization, category 1.

§1910.1200)

### 2.2. Label elements

Label elements (1910.1200) Hazard pictograms



Signal word : Warning

H- and P-phrases : H317 May cause an allergic skin reaction.

P261 vapour Avoid breathing vapours.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 gloves Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water/soap.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 sds Specific treatment (see section 4 on the SDS).
P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container to an official chemical waste depot.

Product name : Premium Type C Gear Lube Page 1/10

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





According to OSHA HazCom 2012, 29 CFR 1910.1200

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w%)	CAS nr.	Additional CAS	Hazards
			nr.	
Polysulfides	1 - < 5	Trade Secret		Flam. Liq. 4; H227
				Skin Sens. 1B; H317
				Aquatic Acute 1; H400
				Aquatic Chronic 1; H410

Occupational exposure limit(s), if relevant, are listed in section 8. The actual concentration has been withheld as a trade secret.

Reference is made to chapter 16 for full text of each relevant H phrase.

### SECTION 4 FIRST-AID MEASURES

## 4.1. Description of first aid measures

First aid measures

Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.

Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up.

Consult a doctor if irritation occurs.

Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.

Ingestion : Do not induce vomiting. Give nothing to drink. Do rinse the mouth. Never give anything by mouth to an

unconscious person. Consult a doctor if victim feels unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

Inhalation : May cause headache, dizziness and a feeling of sickness.

Skin contact : May cause redness and irritation, sensitisation. May produce an allergic reaction. May cause dry skin.

Eye contact : May cause stinging of eyes and redness.

Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause lung damage, sore throat and lack

of breath.

# 4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians : None known.

#### SECTION 5 FIRE-FIGHTING MEASURES

# 5.1. Extinguishing media

Extinguishing media

Suitable : Carbondioxide (CO2). Foam. Dry chemical. Water fog.

Not suitable : Water jet. Use of heavy stream of water may spread fire.

## 5.2. Special hazards arising from the substance or mixture

Special exposure hazards : Will float on water and can be reignited.

Product name : Premium Type C Gear Lube Page 2/10

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





**INFO CARE SDS** 

According to OSHA HazCom 2012, 29 CFR 1910.1200

Hazardous thermal decomposition products

: Carbon monoxide may be evolved if incomplete combustion occurs.

#### 5.3. Advice for firefighters

Special protective equipment for fire-fighters NFPA hazard rating : Use adequate respiratory equipment in case of insufficient ventilation.



### SECTION 6 ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with

spilled or released material. Vapours are heavier than air. Build up (of gasses) in low areas involves risk

of suffocation.

### 6.2. Environmental precautions

Environmental precautions: Avoid release of product into sewers, surface water and/or ground water. In case of large spills: contain

with dike. Waste product should not be allowed to contaminate soil or water.

Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an

authorised waste collection point. Wash away remainder with plenty of water and soap.

### 6.4. Reference to other sections

Reference to other sections: See also section 8.

#### SECTION 7 HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Do

not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage : Keep frost-free, in a cool, dry and well-ventilated place. Keep away from oxidizing agents.

Recommended packaging : Keep only in the original container.

Non recommended

packaging

: PE and PP.

# 7.3. Specific end use(s)

Use : Use only as directed.

# SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Product name : Premium Type C Gear Lube Page 3/10

Date of issue : 2022-07-11 Replaces issue dated : ---





Page 4/10

# According to OSHA HazCom 2012, 29 CFR 1910.1200

## 8.1. Control parameters

Occupational exposure : Oc

: Occupational exposure limits have not been established for this product.

limits

#### Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour	STEL 15 min	Comments	Source
		(mg/m3)	(mg/m3)		
Distillates (petroleum),	US	5	-	Mist	OSHA
hydrotreated heavy paraffinic					
Distillates (petroleum),	US	5	-	inhalable particulate matter	ACGIH
hydrotreated heavy paraffinic					
Distillates (petroleum),	US	5	10	Mist	NIOSH
hydrotreated heavy paraffinic					
Distillates (petroleum),	US	5	10	Mist	NIOSH
hydrotreated heavy paraffinic;					
Baseoil — unspecified					
Distillates (petroleum),	US	5	-	Mist	OSHA
hydrotreated heavy paraffinic;					
Baseoil — unspecified					
Distillates (petroleum),	US	5	-	inhalable particulate matter	ACGIH
hydrotreated heavy paraffinic;				No.	
Baseoil — unspecified			X	(O.X.	

### 8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with

chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

.



Body protection : Wear appropriate protective clothing, overalls or suit, and similar boots. Suitable material: nitril.

Indication of permeation breakthrough time: 6 hours.

Respiratory protection: Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure.

Suitable: gas filter type A (brown), class I or higher on e.g. a facemask.

Hand protection : Wear appropriate safety gloves. Suitable material: nitril. ± 0,5 mm. Indication of permeation

breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses with side shields when there is danger of possible eye contact.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid.
Colour : Green.
Odour : Characteristic.

Product name : Premium Type C Gear Lube

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





According to OSHA HazCom 2012, 29 CFR 1910.1200

Odour threshold : Not known.

pH : Not applicable. Waterfree product.

Solubility in water
Partition coefficient (n-

Not soluble.Not known.Not measured. Not relevant for mixtures.

octanol/water)

Flash point : > 100 °C

Flammability (solid, gas) : Not applicable. Liquid. See flashpoint.

Auto ignition temperature : Not known.

Does not contain substances with a known auto ignition temperature.

Boiling point/boiling range : > 100 °C

Freezing point : < 0 °C

Explosion limits (% in air) : Not known. Lower explosion limit in air (%): 0,9 ( Distillates (petroleum), hydrotreated

heavy paraffinic )

Upper explosion limit in air (%): 7 ( Distillates (petroleum), hydrotreated

heavy paraffinic)

Oxidising properties : Not applicable. Does not contain oxidizing substances.

Decomposition temperature : Not applicable.

Viscosity (20°C) : Not known.

Viscosity (100°C) : 10 mm2/sec

Vapour pressure (20°C) : Not known.

Relative vapour density : > 1 (air = 1)

Relative density (20°C) : 0,87 g/ml Evaporation rate : Not known.

#### SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition : Not known.

products

# SECTION 11 TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.

Product name : Premium Type C Gear Lube Page 5/10

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





Page 6/10

### According to OSHA HazCom 2012, 29 CFR 1910.1200

Inhalation

Acute toxicity : Calculated LC50: > 6,222 mg/l. Ingredients of unknown toxicity: 10 %. ATE: > 5 mg/l. Low toxicity.

Not classified - based on available data, the classification criteria are not met. May cause headache,

dizziness and a feeling of sickness.

Corrosion/irritation : Not classified - based on available data, the classification criteria are not met.

Sensitisation : Does not contain substances classified as respiratory sensitiser. Not classified - based on available

data, the classification criteria are not met.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are

not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not

met.

Skin contact

Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low

toxicity. Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : Not classified - based on available data, the classification criteria are not met. Sensitisation : May cause sensitisation by skin contact. May produce an allergic reaction.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not

met.

Eye contact

Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.

Ingestion

Acute toxicity : Calculated LD50: > 4286 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low

toxicity. Not classified - based on available data, the classification criteria are not met.

Aspiration : Not expected to be an aspiration hazard. Contains a substance/substances with an aspiration hazard.

Not classified - based on available data, the classification criteria are not met.

Corrosion/irritation : May cause a feeling of sickness, stomachache, vomiting and diarrhoea.

Carcinogenicity : Not expected to be carcinogenic. Not classified - based on available data, the classification criteria are

not met.

Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not

met.

Toxicological information:

Chemical name	Property		Method	Test animal	
Polysulfides	LD50 (oral)	> 2000 mg/kg bw	OECD 401	Rat	
	LD50 (dermal)	> 2000 mg/kg bw	OECD 402	Rat	
	Skin sensitisation	Sensitizing.	OECD 406	Guinea pig	

# 11.2. Information on other hazards

Other information : No component of this product present at levels greater than or equal to 0.1% is identified as probable,

possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP.

### SECTION 12 ECOLOGICAL INFORMATION

#### 12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Product name : Premium Type C Gear Lube

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





# According to OSHA HazCom 2012, 29 CFR 1910.1200

Ecotoxicity : Toxic to aquatic organisms. Calculated LC50 (fish): 687 mg/l. Calculated EC50 (waterflea): 6 mg/l.

Contains 0 % of components with unknown hazards to the aquatic environment. May form an oil film on the water surface causing a decline in oxygen content with possible adverse effects for aquatic

organisms.

### 12.2. Persistence and degradability

Persistence – degradability: May cause long-term adverse effects in the aquatic environment.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential : Contains bioaccumulating substances.

12.4. Mobility in soil

Mobility : Adsorbs to soil and has low mobility. Floats on water.

#### 12.7. Other adverse effects

Other adverse effects : Not applicable.

Ecological information:

Chemical name	Property		Method	Test animal
Polysulfides	EC50 (waterflea)	0.24 mg/l	OECD 202	Daphnia magna
	IC50 (algea)	0.838 mg/l	OECD 201	Pseudokirchnerella
				subcapitata
	Ultimate aerobic	13 %	OECD 301 B	
	biodegradation (%)	6, 6,		

#### SECTION 13 DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Product residues : Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat

product residues and non-empty pack as hazardous waste.

Additional warning

: None.

Waste water discharge

Do not dispose of into the environment, drains, sewers or water courses.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied

with.

## SECTION 14 TRANSPORT INFORMATION

### 14.1. UN number or ID number

UN nr. : UN 3082

### 14.2. UN proper shipping name

Transport name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ( Polysulfides )
Transport name (IMDG, : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ( Polysulfides )

IATA)

### 14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

DOT (land)

Product name : Premium Type C Gear Lube Page 7/10

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





Page 8/10

According to OSHA HazCom 2012, 29 CFR 1910.1200

Class : 9 Packaging group : II

Danger label : 9 + the "environmentally hazardous substance" mark.

ERG number : 171





Other information : Not intended for carriage by tank-vessels on inland waterways. Single or combination packagings

containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other requirements provided the packagings meet the

general requirements in §§173.24 and 173.24a (49 CFR 171.4).

IMDG (sea)

Class : 9
Packaging group : III
EmS (fire / spill) : F

: F-A/S-F

Marine pollutant : Yes

Other information : This product is not regulated as a dangerous good when transported in sizes of <= 5 L or <= 5 kg,

provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8 (IMDG

code 37-14, 2.10.2.7).

IATA (air)

Class : 9 ERG code : 9L Packaging group : III

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments.

Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations : OSHA HazCom 2012, 29 CFR 1910.1200 and other Regulations.

United States TSCA (Toxic Substances Control Act) inventory

: All components of this product are in compliance with the inventory listing requirements of the U.S.

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

US State Regulation

California Proposition 65

WARNING: Contains traces of the following substances known to the state of California to cause cancer, birth defects or

other reproductive harm

Chemical name	CAS	Type of toxicity	NSRL or MADL (ug/d)
Cumene	98-82-8	cancer	
Ethylbenzene	100-41-4	cancer	54 (inhalation) 41 (oral)

Product name : Premium Type C Gear Lube

Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





According to OSHA HazCom 2012, 29 CFR 1910.1200

### SECTION 16 OTHER INFORMATION

#### 16.1. Other information

The information in this safety data sheet is compiled in compliance with Hazcom 1910.1200. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (\*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ATE : Acute Toxicity Estimate

CMR : Carcinogenic, Mutagenic or toxic for Reproduction

DOT : Department of Transportation
DSL : Domestic Substances List

GHS : Globally Harmonized System of Classification and Labelling of Chemicals

HPA : Hazardous Products Act

HPR : Hazardous Products Regulations
IATA : International Air Transport Association
IBC code : International Bulk Chemical Code

IMDG : International Maritime Dangerous Goods Code LD50/LC50 : Lethal Dose/Concentration for 50% of a population

MARPOL : International Convention for the Prevention of Pollution From Ships

NO(A)EL : No Observed (Adverse) Effect Level

OECD : Organisation for Economic Co-operation and Development
OSHA : United States Occupational Safety and Health Administration

PBT : Persistent, Bioaccumulative and Toxic

REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals

RID : Regulations concerning the International Carriage of Dangerous Goods by Rail

STP : Sewage Treatment Plant

TWA/STEL : Time-Weighted Average/Short Term Exposure Limit

UN : United Nations

VOC : Volatile Organic Compounds

vPvB : Very Persistent and Very Bioaccumulative

WHMIS : Workplace Hazardous Materials Information System

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc. Also used: OSHA HazCom 2012, 29 CFR 1910.1200.

Full text of H-phrases mentioned in section 3:

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Advice on any training appropriate for workers: none.

Number format : "," used as decimal separator.

Date of preparation or

latest revision

: 2022-07-11

Product name : Premium Type C Gear Lube Page 9/10
Date of issue : 2022-07-11 Replaces issue dated : --- INFO CARE SDS





According to OSHA HazCom 2012, 29 CFR 1910.1200

End of safety data sheet.



Product name Date of issue

: Premium Type C Gear Lube

: 2022-07-11

: AOATT.B-VWCC

Replaces issue dated

Page 10/10 INFO CARE SDS