

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture **Product Name: Bug-Off Product Code: 927XX Intended Use of the Product** Cleaner Name, Address, and Telephone of the Responsible Party Company Star brite Inc. 4041 SW 47th Avenue Fort Lauderdale, FL 33314 (954)587-6280 www.starbrite.com **Emergency Telephone Number Emergency Number** : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC) **SECTION 2: HAZARDS IDENTIFICATION Classification of the Substance or Mixture Classification (GHS-US)** Eye Dam. 1 H318 Skin Sens. 1 H317 Full text of H-phrases: see section 16 **Label Elements GHS-US Labeling** Hazard Pictograms (GHS-US) Signal Word (GHS-US) : Danger Hazard Statements (GHS-US) : H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. **Precautionary Statements (GHS-US)** : P261 - Avoid breathing vapors, mist, or spray. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves, protective clothing, and eye protection. P302+P352 - If on skin: Wash with plenty of water. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a poison center or doctor. P321 - Specific treatment (see section 4 on this SDS). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Aquatic Acute 3 H402 H402 - Harmful to aquatic life. P273 - Avoid release to the environment.

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Version: 3.0

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mivturo	

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Tetrasodium EDTA	(CAS No) 64-02-8	1 - 5	Comb. Dust, H232
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Eye Dam. 1, H318
			Aquatic Acute 2, H401
Alcohols, C9-11, ethoxylated	(CAS No) 68439-46-3	1 - 5	Acute Tox. 4 (Oral), H302
-			Eye Dam. 1, H318
Dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	0.1 – 1	Flam. Liq. 4, H227
Sodium xylene sulfonate	(CAS No) 1300-72-7	0.1 - 1	Eye Irrit. 2A, H319
Nitrilotriacetic acid trisodium salt†	(CAS No) 5064-31-3	< 0.1	Acute Tox. 4 (Oral), H302
		0.1 - 1	Eye Irrit. 2A, H319
			Carc. 2, H351
Sodium hydroxide	(CAS No) 1310-73-2	< 0.1	Met. Corr. 1, H290
		0.1 - 1	Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Octylphenol ethoxylate	(CAS No) 9036-19-5	0.1 - 1	Acute Tox. 4 (Oral), H302
			Eye Dam. 1, H318
			Aquatic Acute 1, H400
			Aquatic Chronic 3, H412
D-Limonene	(CAS No) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Skin Sens. 1, H317
			Asp. Tox. 1, H304
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

*More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

[†] The carcinogen classification is applicable to the overall product only if this ingredient is >= 5% of the mixture. The Carc. 2 classification does not apply for this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

Conord Nover give entiting by mouth to an uncord

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area.

Skin Contact: Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER/doctor/physician if you feel unwell.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage. May cause an allergic skin reaction.

Inhalation: May cause irritation to the respiratory tract.

Skin Contact: May cause an allergic skin reaction. May cause skin irritation.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva. Can cause blindness.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Dry powder, alcohol-resistant foam, water in large amounts, carbon dioxide (CO₂).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all eyes and skin contact and do not breathe vapor, mist, and spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Eliminate ignition sources. Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Caustic products. Alkaline substances. Halogens.

Specific End Use(s)

Cleaner.

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Sodium hydroxide (1310-73-2)				
	ACGIH Ceiling (mg/m ³)	2 mg/m ³		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³		
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³		
USA IDLH	US IDLH (mg/m ³)	10 mg/m ³		
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³		
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³		
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³		
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³		
	OEL Ceiling (mg/m ³)	2 mg/m ³		
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³		
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³		
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³		
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³		
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³		
Québec	PLAFOND (mg/m ³)	2 mg/m ³		
	OEL Ceiling (mg/m ³)	2 mg/m ³		
Yukon	OEL Ceiling (mg/m ³)	2 mg/m^3		
Dipropylene głycol monomet		~ mg, m		
USA ACGIH	ACGIH TWA (ppm)	100 ppm		
	ACGIH STEL (ppm)	150 ppm		
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure		
USA AUGII	Acom chemical category	by the cutaneous route		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	600 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm		
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	600 mg/m ³		
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm		
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	900 mg/m ³		
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm		
USA IDLH	US IDLH (ppm)	600 ppm		
Alberta	OEL STEL (mg/m³)	909 mg/m ³		
Alberta	OEL STEL (ppm)	150 ppm		
Alberta	OEL TWA (mg/m ³)	606 mg/m ³		
Alberta	OEL TWA (ppm)	100 ppm		
British Columbia	OEL STEL (ppm)	150 ppm		
British Columbia	OEL TWA (ppm)	100 ppm		
Manitoba	OEL STEL (ppm)	150 ppm		
Manitoba	OEL TWA (ppm)	100 ppm		
New Brunswick	OEL STEL (mg/m ³)	909 mg/m ³		
New Brunswick	OEL STEL (ppm)	150 ppm		
New Brunswick	OEL TWA (mg/m ³)	606 mg/m ³		
New Brunswick	OEL TWA (ppm)	100 ppm		
Newfoundland & Labrador	OEL STEL (ppm)	150 ppm		
	OEL TWA (ppm)	100 ppm		
Nova Scotia	OEL STEL (ppm)	150 ppm		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m ³)	909 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	606 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	909 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m ³)	606 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VECD (mg/m ³)	909 mg/m ³
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m ³)	606 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Enne a surray Constant la		

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Consumer Exposure Controls:** Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
Information on Basic Physical and Chemical Properties			
Physical State	: Liquid		
Appearance	: Orange Liquid		
Odor	: Characteristic		
Odor Threshold	: Not available		
рН	: 12		
Evaporation Rate	: Not available		
Melting Point	: 0 °C (32 °F)		
Freezing Point	: Not available		
Boiling Point	: 100 °C (212 °F)		
Flash Point	: Not available		
Auto-ignition Temperature	: Not available		
Decomposition Temperature	: Not available		
Flammability (solid, gas)	: Not available		
Lower Flammable Limit	: Not available		
Upper Flammable Limit	: Not available		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Vapor Pressure	:	Not available
Relative Vapor Density at 20 °C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	1.0225
Solubility	:	Soluble in water
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
Explosion Data – Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under normal conditions.

Hazardous polymerization will not occur. **Possibility of Hazardous Reactions:**

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Sources of ignition. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Caustic products. Alkaline substances. Halogens.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Aldehydes. Ketones. Organic acids. Sulfur oxides. Metal oxides. Sodium oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

ID50 and IC50 Data: Not available Skin Corrosion/Irritation: Not classified. **pH:** 12 Serious Eye Damage/Irritation: Causes serious eye damage. **pH:** 12 **Respiratory or Skin Sensitization:** May cause an allergic skin reaction. Germ Cell Mutagenicity: Not classified Teratogenicity: Not classified Carcinogenicity: Not classified Specific Target Organ Toxicity (Repeated Exposure): Not classified **Reproductive Toxicity:** Not classified Specific Target Organ Toxicity (Single Exposure): Not classified **Aspiration Hazard:** Not classified Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract. Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. May cause skin irritation. Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva. Can cause blindness. Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. Chronic Symptoms: None known. Information on Toxicological Effects - Ingredient(s) ID50 and LC50 Data: Tetrasodium EDTA (64-02-8) **LD50 Oral Rat** 1780 mg/kg ATE US (dust, mist) 1.50 mg/l/4h Nitrilotriacetic acid trisodium salt (5064-31-3) **LD50 Oral Rat** 1740 mg/kg LD50 Dermal Rabbit > 2000 mg/kg **LC50 Inhalation Rat** > 5 mg/l/4h Dipropylene glycol monomethyl ether (34590-94-8) **LD50 Oral Rat** 5230 mg/kg 08/06/2015 IEATT.B-CC EN (English US) 6/13

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

	5	
ID50 Dermal Rabbit	9500 mg/kg	
Alcohols, C9-11, ethoxylated (68439-46-3)		
ID50 Oral Rat	1400 mg/kg	
LD50 Dermal Rat	> 2 g/kg	
D-Limonene (5989-27-5)		
ID50 Oral Rat	4400 mg/kg	
ID50 Dermal Rabbit	> 5 g/kg	
ATE US (oral)	4,400.00 mg/kg body weight	
Octylphenol ethoxylate (9036-19-5)		
ID50 Oral Rat	1700 mg/kg	
Sodium xylene sulfonate (1300-72-7)		
ID50 Oral Rat	> 5000 mg/kg	
ID50 Dermal Rabbit	> 2000 mg/kg	
Nitrilotriacetic acid trisodium salt (5064-31-3)		
IARC Group	2B	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
D-Limonene (5989-27-5)		
IARC Group	3	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.	
SECTION 12: ECOLOGICAL INFORMATION		
<u>Toxicity</u>		

Ecology - **General:** Harmful to aquatic life.

Ecology - General: Harmful to aquatic me.				
Tetrasodium EDTA (64-02-8)				
LC 50 Fish 1	486 (Exposure time: 96h - Species: Lepomis macrochirus)			
EC50 Daphnia 1	625 mg/l (Exposure time: 24 h - Species: Daphnia magna)			
ErC50 (algae)	3 mg/l (exposure time: 96 h - Species:Green Algae)			
Sodium hydroxide (1310-73-2)				
LC50 Fish 1	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])			
EC50 Daphnia 1	40 mg/l			
Nitrilotriacetic acid trisodium salt (5064	1 -31-3)			
LC 50 Fish 1	93 - 170 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
EC50 Daphnia 1	560 - 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
LC 50 Fish 2	175 - 225 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])			
Dipropylene glycol monomethyl ether	Dipropylene glycol monomethyl ether (34590-94-8)			
LC 50 Fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)			
D-Limonene (5989-27-5)				
LC50 Fish 1	0.619 - 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC 50 Fish 2	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)			
Octylphenol ethoxylate (9036-19-5)				
IC50 Fish 1	7.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])			
EC50 Daphnia 1	8.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [static])			
ErC50 (algae)	rC50 (algae) 0.21 mg/l (Exposure time: 96 h - Species: Selenastrum Green Algae)			
Sodium xylene sulfonate (1300-72-7)				
EC50 Daphnia 1	50 Daphnia 1 > 1020 ml/l (Exposure time: 48 h - Species: Daphnia magna [Flow-through])			
Persistence and Degradability				
Bug-Off				
Persistence and Degradability	Not established.			
· · · · · · · · · · · · · · · · · · ·				

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Dipropylene glycol monomethyl ether (34590-94-8)		
Persistence and Degradability	Persistence and Degradability Readily biodegradable.	
Bioaccumulative Potential		
Bug-Off		
Bioaccumulative Potential	Bioaccumulative Potential Not established.	
Tetrasodium EDTA (64-02-8)		
Log Pow	5.01 (calculated)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Log Pow	-0.064 (at 20 °C)	
Bioaccumulative Potential	Not expected to bioaccumulate.	
Mobility in Soil Not available		
Other Adverse Effects		

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way. Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport.

UN Proper Shipping Name Not regulated for transport.

Transport Hazard Class(es) Not regulated for transport.

Additional Information Not available

Marine Pollutant: No

Transport by sea Not regulated for transport.

Air transport Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Bug-Off		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
Tetrasodium EDTA (64-02-8)		
Listed on the United States TSCA (Toxic Substances Control Act)) inventory	
Sodium hydroxide (1310-73-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Nitrilotriacetic acid trisodium salt (5064-31-3)		
Listed on the United States TSCA (Toxic Substances Control Act)) inventory	
Dipropylene glycol monomethyl ether (34590-94-8)		
Listed on the United States TSCA (Toxic Substances Control Act)) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test	
	rule under TSCA.	
Alcohols, C9-11, ethoxylated (68439-46-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
D-Limonene (5989-27-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Octylphenol ethoxylate (9036-19-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Sodium xylene sulfonate (1300-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

<u>US State Regulations</u>

Tetrasodium EDTA (64-02-8)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Sodium hydroxide (1310-73-2)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities

- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Louisiana Reportable Quantity List for Pollutants

U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1

- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits Ceilings
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Ceilings
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits Ceilings
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits Ceilings
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Ceilings
- U.S. Washington Permissible Exposure Limits Ceilings
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Nitrilotriacetic acid trisodium salt (5064-31-3)

U.S. - Illinois - Toxic Air Contaminant Carcinogens

U.S. - Illinois - Toxic Air Contaminants

Safety Data Sheet			
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations			
RTK - U.S Massachusetts - Right To Know List			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			
Dipropylene glycol monomethyl ether (34590-94-8)			
U.S Connecticut - Hazardous Air Pollutants - HLVs (30 min)			
U.S Connecticut - Hazardous Air Pollutants - HLVs (8 hr)			
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations			
U.S Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)			
U.S Idaho - Occupational Exposure Limits - TWAs			
RTK - U.S Massachusetts - Right To Know List			
U.S Michigan - Occupational Exposure Limits - Skin Designations			
U.S Michigan - Occupational Exposure Limits - STELs			
U.S Michigan - Occupational Exposure Limits - TWAs			
U.S Minnesota - Hazardous Substance List			
U.S Minnesota - Permissible Exposure Limits - Skin Designations			
U.S Minnesota - Permissible Exposure Limits - STELs U.S Minnesota - Permissible Exposure Limits - TWAs			
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour			
U.S New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual			
RTK - U.S New Jersey - Right to Know Hazardous Substance List			
U.S New York - Occupational Exposure Limits - Skin Designations			
U.S New York - Occupational Exposure Limits - TWAs			
U.S North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour			
U.S North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour			
U.S Oregon - Permissible Exposure Limits - Skin Designations			
U.S Oregon - Permissible Exposure Limits - TWAs			
RTK - U.S Pennsylvania - RTK (Right to Know) List			
U.S Tennessee - Occupational Exposure Limits - Skin Designations			
U.S Tennessee - Occupational Exposure Limits - STELs			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			
U.S Vermont - Permissible Exposure Limits - Skin Designations U.S Vermont - Permissible Exposure Limits - STELs			
U.S Vermont - Permissible Exposure Limits - STEIS U.S Vermont - Permissible Exposure Limits - TWAs			
U.S Washington - Permissible Exposure Limits - Skin Designations			
U.S Washington - Permissible Exposure Limits - STELs			
U.S Washington - Permissible Exposure Limits - TWAs			
Alcohols, C9-11, ethoxylated (68439-46-3)			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			
D-Limonene (5989-27-5)			
U.S Maine - Chemicals of High Concern			
U.S Minnesota - Chemicals of High Concern			
U.S Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			
Octylphenol ethoxylate (9036-19-5)			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			
Sodium xylene sulfonate (1300-72-7)			
U.S Texas - Effects Screening Levels - Long Term			
U.S Texas - Effects Screening Levels - Short Term			

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Canadian Regulations

Bug-Off	1	
WHMIS Classification	Class E - Corrosive Material	
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
	J	
Tetrasodium EDTA (64-02-8)		
Listed on the Canadian DSL (I	Domestic Substances List)	
WHMIS Classification	Class E - Corrosive Material	
	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Sodium hydroxide (1310-73-2	2)	
Listed on the Canadian DSL (I	Oomestic Substances List)	
Listed on the Canadian IDL (Ir	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class E - Corrosive Material	
Nitrilotriacetic acid trisodiun	n salt (5064-31-3)	
Listed on the Canadian DSL (I	Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
	Class E - Corrosive Material	
Dipropylene glycol monomet	thyl ether (34590-94-8)	
Listed on the Canadian DSL (I	Domestic Substances List)	
Listed on the Canadian IDL (Ir	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class B Division 3 - Combustible Liquid	
Alcohols, C9-11, ethoxylated	(68439-46-3)	
Listed on the Canadian DSL (I		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
D-Limonene (5989-27-5)		
Listed on the Canadian DSL (I	Domestic Substances List)	
Listed on the Canadian IDL (Ir		
IDL Concentration 1 %		
WHMIS Classification	Class B Division 3 - Combustible Liquid	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
Octylphenol ethoxylate (903	6-19-5)	
Listed on the Canadian DSL (I		
Listed on the Canadian IDL (Ir	ngredient Disclosure List)	
IDL Concentration 1 %		
WHMIS Classification	Class E - Corrosive Material	
Sodium xylene sulfonate (13	00-72-7)	
Listed on the Canadian DSL (I		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS		
contains all of the information		
	DRMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION	

: 08/06/2015

Revision Date

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Fuil Text Phrases:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation: gas)	Acute toxicity (inhalation: gas) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H226	Flammable liquid and vapor
H227	Combustible liquid
H232	May form combustible dust concentrations in air
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<u> </u>	• •	
NFPA Health Hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.	
NFPA Fire Hazard	: 1 - Must be preheated before ignition can occur.	
NFPA Reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	

Party Responsible for the Preparation of This Document Starbrite® Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2