

MATERIAL SAFETY DATA SHEET

SECTION 1 – SUPPLIER INFORMATION

Product Name: Star brite Motor Oil SAE Heavy Duty 40

Product Number: 17132, 17100, 17105, 171G55

Supplier's Name: Star brite Distributing, Inc.
4041 S. W. 47 Avenue
Ft. Lauderdale, FL 33314

Information Phone: 954-587-6280
Emergency Phone: (Chemtrec) 800-424-9300 or 703-527-3887

Date prepared: June 18, 2005

SECTION 11 – HAZARDOUS INGREDIENT INFORMATION

HAZARD RATING

4-Extreme
3-High
2-Moderate
1-Slight
0-Insignificant

RATING

Health – 1
Flammability – 1
Reactivity – 0
CAS # - None – Mixture

Toxic and Hazardous Ingredients:

<u>Components</u>	<u>CAS#</u>	<u>TLV</u>	<u>Wt.%</u>
Zinc Alkyldithiophosphate	68649-42-3	Not Determined	0.5 – 1.0
Diphenylamine	122-39-4	10.0 mg/cubic m.	0.01 – 0.1

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

Chemical Name: Petroleum Hydrocarbon plus Additives

Formula:	Not applicable	Melting Point (pour point):	<-15° C (5° F)
Form:	Liquid	Solubility in Water(by weight %):	0% @ 20° C
Appearance:	Liquid	Volatile (by weight %):	0
Odor:	Motor oil	Evaporation Rate:	0
Color:	Amber	Vapor Pressure (mm Hg @ 20° C):	0
Specific Gravity at 60° F:	0.888	Vapor Density (air=1):	Not volatile
Boiling Point:	>300° C (572° F)	pH (as is):	Not applicable
		Viscosity SUS @ 100° F:	630

SECTION IV – FIRE AND EXPLOSION DATA

Special Fire Fighting Procedures:	Do not use water, except as fog
Unusual Fire & Explosion Hazards:	None
Flashpoint (ASTM D92):	216° C (421° F)
Flammable Limits %:	Not applicable
Extinguishing Agents:	Dry chemical or water fog or CO ₂ or foam. Exposed material may be cooled with water.

SECTION V – REACTIVITY DATA

Stability:	Stable
Conditions to avoid:	High temperatures
Incompatibility:	Strong oxidizers such as hydrogen peroxide, bromine and chromic acid.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide from burning. Oxides of phosphorous. Oxides of sulfur.

Product Name: Star brite Motor Oil SAE Heavy Duty 40

Product Number: 17132, 17100, 17105, 171G55

SECTION VI – HEALTH HAZARD DATA/FIRST AID

EMERGENCY FIRST AID PROCEDURES:

Eyes: Immediately flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water. Prolonged skin contact may cause dermatitis or irritation.

Inhalation: Remove victim to fresh air. Call a physician.

If Swallowed: **Contact a physician immediately.**

SECTION VII – PRECAUTIONS FOR SAFE HANDLING

Precautions to be taken in Handling and Storage: Do not handle or store at temperatures over 38° C or 100° F.

Maximum Storage Temperature: 38° C (100° F)

SECTION VIII – SPECIAL PROTECTION CONTROL MEASURES

Ventilation Type Required (Local, mechanical, special):	None, unless oil mist exceeds 5mg/m ³
Respiratory Protection (Specify Type):	None, unless oil mist exceeds 5mg/ m ³
Protective Gloves:	Neoprene or nitrile rubber
Eye Protection:	Chemical safety goggles with side shields or face shield
Other Protective Equipment:	Laundry soiled clothes before reuse.

SECTION IX – HANDLING OF SPILLS AND LEAKS

Procedures for Clean-up: Transfer bulk of material into another container. Absorb with inert material such as earth, sand, or vermiculite. Sweep up and dispose remaining material in accordance with local, state and federal regulations.

Waste Disposal: Dispose of in accordance with all applicable federal, state and local regulations.

SECTION X – TOXICOLOGICAL/ECOLOGICAL INFORMATION

Permissible Concentration:	Oil mist mineral 5mg/m m ³ . (OSHA and NIOSH)
Chronic Effects of Overexposure:	Prolonged skin contact may cause dermatitis or skin irritation
Acute Toxicological Properties: Oral LD50:	(rats) >5,000 mg/kg
Dermal LD50:	(rabbits) > 2,000 mg/kg
Carcinogenicity:	Not carcinogenic under IARC

SECTION XI – TRANSPORTATION DATA

Call for information

SECTION XII – REGULATORY INFORMATION

All components listed on TSCA inventory.

Product Name: Star brite Motor Oil SAE Heavy Duty 40

Product Number: 17132, 17100, 17105, 171G55

SECTION XIII – USER INFORMATION

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable Federal, State and Local laws and regulations.

Relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading, this information relates to the material designated and may not be valid for such material used in combination with any other materials or in any process.

New and used motor oils have been tested for potential Carcinogenicity in laboratory mice. Only used motor oils were shown to cause skin cancer when repeatedly applied to mice without any effort to remove the material between applications. Strict compliance to the occupation control procedures outlined in the data sheet is believed to be adequate protection from such hazards.