

## MATERIAL SAFETY DATA SHEETS

MANUFACTURER  
Star brite Distributing  
4041 S.W. 47 Avenue  
Ft. Lauderdale, FL 33314

EMERGENCY TELEPHONE NO.  
800-424-9300 or 703-527-3887 Chemtrec

INFORMATION TELEPHONE NO.  
800-327-8583

Date of Preparation  
May 4, 2006

### 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NUMBER:** 27010, 27032, 27000, 27005, 27055  
**PRODUCT NAME:** Star brite High Viscosity 80W90 Gear Lube GL-5

### 2: COMPOSITION/INFORMATION ON INGREDIENT/HAZARDOUS INGREDIENTS

COMPONENTS	CAS NO.	%	HAZARD DATA
1) Highly Refined Paraffinic Petroleum Oils	64741-88-4	>90	Oral (LD50): >5000 mg/kg Dermal (LD50): > 2000 mg/kg
2) Petroleum Additives	Mixture	<15	
<b>HAZARDOUS INGREDIENTS:</b>	NONE		
<b>HAZARDOUS PER 29 CFR 1916.1200:</b>	NO		

### 3: HAZARDOUS IDENTIFICATION

**Routes of Entry:** Skin Contact

**Target Organs:** Skin

**Irritancy:** This product can cause mild, transient, eye irritation with short-term contact with liquid or sprays.

**Reproductive Effects:** N/A

**Cancer Information:** This product does not contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC, or NTP.

### 4: FIRST AID MEASURES

**Eyes:** Check for and remove contact lenses. Flush eye with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness, or pain persists.

**Dermal:** Remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with soap and water. Seek medical attention if tissue appears damaged or if irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods.

**Ingestion:** Do not induce vomiting unless directed to by a physician. Do not give anything to drink unless directed to by a physician. Never give anything by mouth to a person who is not fully conscious. Seek medical attention immediately.

**Inhalation:** Move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If breathing is difficult, 100 percent humidified oxygen should be administered by a qualified individual. Seek medical attention immediately. Keep the affected individual warm and at rest.

**Injection:** Injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.

**5: FIRE FIGHTING MEASURES**

<b>Flash Point, °C (°F):</b>	180°C (356°F)
<b>Flammable Limits (% By Volume):</b>	<b>Lower</b> No Data <b>Upper</b> No Data
<b>Extinguishing Media:</b>	Use dry chemical, foam, carbon dioxide or water fog.
<b>Special Fire Fighting Procedures:</b>	N/A
<b>Autoignition:</b>	N/A
<b>Explosion Data:</b>	N/A
<b>NFPA Rating:</b>	<b>Health: 1   Flammability: 1   Reactivity: 0</b>

**6: ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spills as soon as possible. In natural, environments seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

**7: HANDLING AND STORAGE**

**Handling Procedures:** Avoid water contamination and extreme temperatures to minimize product degradation. Empty containers may contain product residues that can ignite with explosive force. Do not pressures, cut weld, braze solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

**Storage Procedures:** Keep containers closed. Do not store with strong oxidizing agents. Do not store at temperatures above 120°F or in direct sunlight for extended period of time. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

**8: EXPOSURE CONTROLS /PERSONAL PROTECTION**

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. An eye wash station and safety shower should be located near the work-station.

**Glove Protection:** Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. Use heat protective gloves when handling product at elevated temperatures.

**Eye Protection:** Safety glasses equipped with side shields should be adequate protection under most conditions of use. Wear goggles and/or face shield if splashing or spraying is likely, especially if material is heated above 125°F (or 51°C). Have suitable eye wash water available.

**Respiratory protection:** Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a niosh-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. In accordance with OSHA requirements (29 CFR 1910.134).

**Clothing Recommendations:** Avoid prolonged and/or repeated skin contact, especially after this product has been used in a crankcase. If splashing or spraying is expected, chemical-resistant protective clothing should be worn. This might include long-sleeves, apron, slicker suit, boots and additional facial protection. If general contact occurs, promptly remove soaked clothing and take a shower.

**9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Dark Amber Liquid
<b>Odor:</b>	Mild Petroleum Odor
<b>Vapor Pressure, mm Hg (25°C)</b>	<0.0001
<b>Vapor Density:</b>	12+ (AIR) = 1)
<b>Melting Point:</b>	Not Available
<b>Boiling Point, 760 mm hg, °C</b>	Not Available
<b>Solubility in Water</b>	Insoluble in cold water
<b>Specific Gravity:</b>	0.88 (water = 1)
<b>Evaporation Rate:</b>	N/A
<b>Viscosity 40°C (100°C)</b>	148 CST @ 40°C
<b>Molecular Weight:</b>	N/A
<b>Percent Volatile:</b>	Negligible Volatility

**10: STABILITY AND REACTIVITY**

<b>Stability:</b>	Stable
<b>Incompatibility:</b>	Strong Oxidizers
<b>Polymerization:</b>	Not expected to occur
<b>Thermal Decompositions:</b>	Co <sub>2</sub> , Co. smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, nitrogen, phosphorus and zinc.

**11: TOXICOLOGICAL INFORMATION**

<b>Eye irritation:</b>	This product can cause mild, transient, eye irritation with short-term contact with liquid or sprays.
<b>Dermal Irritation:</b>	This material can cause mild, transient skin irritation with short-term exposure.
<b>Inhalation Toxicity</b>	No significant adverse health effects are expected to occur upon short-term exposure to this product. Aspiration of liquid into the lungs can cause severe lung damage or death.
<b>Ingestion Irritation:</b>	If swallowed, no significant adverse health effects are anticipated ingestion can cause mild irritation to the digestive tract or cause a laxative effect.
<b>Injection Sensation:</b>	Injection under the skin, in muscle, or into the blood stream can cause irritation, inflammation, swelling, fever and systemic effects and mild central nervous system depression, injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.
<b>Chronic Exposure Symptoms:</b>	Prolonged or repeated contact can cause mild skin irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne.

**12: HEALTH INFORMATION**

<b>HMIS CODE</b>	<b>Health:</b> <u>1</u>	<b>FIRE:</b> <u>1</u>	<b>Reactivity:</b> <u>0</u>
No. Highly Toxic	No. Sensitizer		
No. Toxic	No. Reproductive Effects		
No. Corrosive	No. Mutagen		
No. Irritant			

**13: DISPOSAL CONSIDERATIONS**

<b>Waste Disposal:</b>	It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal. Determine compliance status with all applicable requirements prior to disposal.
------------------------	---

**14: TRANSPORT INFORMATION**

Call for information

**15 REGULATORY INFORMATION**

**SARA Section 313 – Toxic Chemicals:**

This product does not contain chemical under SARA Section 313 and 40 CFR part 372.

<u>COMPONENTS</u>	<u>CAS#</u>	<u>%</u>
-------------------	-------------	----------

**SARA Section 311 – Hazard Categories:**

This product may meet one more of the criteria of the hazard categories defined in 40 CFR Part 370 as established by Section 311 and 312 of SARA as indicated below.

NO	Immediate (Acute) Health Hazard	No	Sudden Release of Pressure Hazard
NO	Delayed (Chronic) Health Hazard	No	Reactive Hazard
NO	Fire Hazard		

**SARA Section 302 – Extremely Hazardous waste:**

This product is known to contain any components in concentrations greater than one percent that are listed as Extremely Hazardous Substances in 40 CFR Part 355 pursuant to the requirements of Section 302(a) of SARA.

**Clean Water Act (CWA)**

Under the CWA, discharges of crude oil and petroleum products to surface water without proper Federal and State permits must be reported immediately to the National Response Center at (800) 424-8002.

**CERCLA Hazardous Substances:**

As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically listed or designated as a hazardous substance.

**U.S. TSCA Inventory**

All components of this material are on the U.S. TSCA Inventory or not required to be listed on the U.S. TSCA Inventory.

**16: OTHER INFORMATION**

The information in the Material Safety Data Sheet should be provided to all who will use, handle, store, transport, or otherwise be exposed to this product. This information has been prepared for the guidance of Plant Engineering, Operations and Management and for the persons working with or handling this product. Star brite Distributing believes this information to be reliable and up to date as of the date of publication, but makes no warranty that it is.

<b>NFPA Hazard Rating</b>	least – 0 slight – 1	moderate – 2	high – 3 extreme – 4
<b>MIS Health Rating</b>	least – 0 slight – 1	moderate – 2	high – 3 extreme – 4